

SPECIFICATION SHEET



12 LITRE UN POLYCOMPOSITE DRUM (Reduced top for stacking)

A Stackable UN Steel drum with a HDPE liner suitable for chemical products and food contact.

Specification

Outer Steel

- Closure Security closure V1G2 made from PP in the top
- Gasket PE synthetic rubber 5mm between inner liner wall
- Handle 5mm Galvanised Wire Handle
- Body Straight Sided
- Top / Bottom Double seamed to body.
- External Coating RAL 5010
- Embossed Base UN6HA1/X/300/year
- Reduced Top 222mm Outside Diameter

Internal Plastic Liner

- Inner Liner Tighthead inner liner made from HDPE Lupolen 4261A
- Liner Weight 380g
- Closure 2" Threaded Plug
- Closing Torque Min 12 Nm



Volume	Steel Plate Thickness (mm)			Weight	UN Approval
	Top End	Body	Bottom		
12 Litre Nominal	0.5mm	0.5mm	0.5mm	1.85 kg	UN6HAA1/X/300/**/ D/BAM3039-GDH

Qty Per Pallet	Pallet Size	Shrink Wrap	Strap	Pallet Hood	Layer Pad	Foam Wrap
100	CP1	Yes	NO	NO	NO	NO

N.B. Users should satisfy themselves that the type of drum including all material closures and coatings are suitable and compatible with the products to be contained.

Information on terms & conditions can be found on www.jamesgcarrick.com

This document is uncontrolled when printed

James G Carrick & Co Ltd
450 Petershill Road
Springburn
Glasgow
G21 4PB

Tel +44 141 558 6008
Fax +44 141 557 0318
e mail sales@jamesgcarrick.com