

# SPECIFICATION SHEET



## 30 LITRE UN POLYCOMPOSITE DRUM (Reduced top for stacking)

A Stackable UN Steel drum with a HDPE liner suitable for chemical products and food contact.

### Specification

#### Outer Steel

- Closure 3V1-2"/BCS56x4/PP/Poly
- Gasket PE synthetic rubber 5mm between inner liner wall
- Handle 5mm Galvanised Wire Handle
- Body 2 x Rolling Hoops
- Top / Bottom Double seamed to body.
- External Coating RAL 5010
- Embossed Base UN6HA1/X1.6/300/year
- Reduced Top 272mm Outside Diameter

#### Internal Plastic Liner

- Inner Liner Tighthead inner liner made from HDPE Lupolen 4261A
- Liner Weight 750g
- Closure 2" Threaded Plug
- Closing Torque Min 12 Nm



Volume	Steel Plate Thickness (mm)			Weight	UN Approval
	Top End	Body	Bottom		
30 Litre Nominal	0.5mm	0.5mm	0.5mm	3.5 kg	UN6HAA1/X1.6/300/**/ D/BAM4647-GDH

Qty Per Pallet	Pallet Size	Shrink Wrap	Strap	Pallet Hood	Layer Pad	Foam Wrap
56	CP1	Yes	NO	NO	NO	NO

*N.B. Users should satisfy themselves that the type of drum including all material closures and coatings are suitable and compatible with the products to be contained.*

*Information on terms & conditions can be found on [www.jamesgcarrick.com](http://www.jamesgcarrick.com)*

This document is uncontrolled when printed

James G Carrick & Co Ltd  
450 Petershill Road  
Springburn  
Glasgow  
G21 4PB

Tel +44 141 558 6008  
Fax +44 141 557 0318  
e mail sales@jamesgcarrick.com

Issue Date 1<sup>st</sup> August 2011

Issue No 1