

SPECIFICATION SHEET



6 LITRE UN POLYCOMPOSITE DRUM (Reduced top for stacking)

A stackable UN Steel drum with a HDPE liner suitable for chemical products and food contact.

Specification

Outer Steel

- Closure Security closure V1G2 made from PP in the top
- Gasket PE synthetic rubber 5mm between inner liner wall
- Handle 5mm Galvanised Wire Handle
- Body Straight Sided
- Top / Bottom Double seamed to body.
- External Coating RAL 5010
- Embossed Base UN6HA1/X/300/year
- Reduced Top 222mm Outside Diameter



200 mm

← 235 mm →

Internal Plastic Liner

- Inner Liner Tighthead inner liner made from HDPE Lupolen 4261A
- Liner Weight 250g
- Closure 2" Threaded Plug
- Closure Torque Min 12 Nm

| Volume | Steel Plate Thickness (mm) | | | Weight | UN Approval |
|-----------------|----------------------------|-------|--------|------------------|------------------------------------|
| | Top End | Body | Bottom | | |
| 6 Litre Nominal | 0.5mm | 0.5mm | 0.5mm | 1.3 kg +/- 5% | UN6HAA1/X/300/**/ D/BAM3039-GDH |

| Qty Per Pallet | Pallet Size | Shrink Wrap | Strap | Pallet Hood | Layer Pad | Foam Wrap |
|----------------|-------------|-------------|-------|-------------|-----------|-----------|
| 100 | CP1 | Yes | NO | NO | NO | NO |

N.B. Users should satisfy themselves that the type of drum including all material closures and coatings are suitable and compatible with the products to be contained.

Information on terms & conditions can be found on www.jamesgcarrick.com

This document is uncontrolled when printed.

James G Carrick & Co Ltd
450 Petershill Road
Springburn
Glasgow
G21 4PB

Tel +44 141 558 6008
Fax +44 141 557 0318
e mail sales@jamesgcarrick.com