

SPECIFICATION SHEET



60 LITRE UN POLYCOMPOSITE DRUM (Reduced top for stacking)

A stackable UN Steel drum with a HDPE liner suitable for chemical products and food contact.

Specification

Outer Steel

- Closure 3V1-2"/BCS56x4/PP/Poly
- Gasket PE synthetic rubber 5mm between inner liner wall
- Handle 2 x 5mm Galvanised Wire Handle
- Body 2 x Rolling Hoops
- Top / Bottom Double seamed to body.
- External Coating RAL 5010
- Embossed Base UN6HA1/X1.6/250/year
- Reduced Top 346mm Outside Diameter

Internal Plastic Liner

- Inner Liner Tighthead inner liner made from HDPE Lupolen 4261A
- Liner Weight 1100g
- Closure 2" Threaded Plug
- Closing Torque Min 12 Nm



Volume	Steel Plate Thickness (mm)			Weight	UN Approval
	Top End	Body	Bottom		
60 Litre Nominal	0.5mm	0.5mm	0.5mm	5.2 kg +/- 5%	UN6HAA1/X1.3/250/**/ D/BAM1537-GDH
	+/- .05mm	+/- .05mm	+/- .05mm		

Qty Per Pallet	Pallet Size	Shrink Wrap	Strap	Pallet Hood	Layer Pad	Foam Wrap
24	CP1	Yes	NO	NO	NO	NO

N.B. Users should satisfy themselves that the type of drum including all material closures and coatings are suitable and compatible with the products to be contained.

Information on terms & conditions can be found on www.jamesgcarrick.com

This document is uncontrolled when printed.

James G Carrick & Co Ltd
450 Petershill Road
Springburn
Glasgow
G21 4PB

Tel +44 141 558 6008
Fax +44 141 557 0318
e mail sales@jamesgcarrick.com