

SPECIFICATION SHEET

UN 1 TIGHT HEAD STEEL DRUM



15 LITRES (Reduced Head for Stacking)

A steel tight head drum manufactured in accordance with the UN packaging specification, and satisfies the provisions of the packaging and packaging waste directive 94/62/EC.

Tested for Packaging Groups I, II, III.

Closure

G2 & G ¾ Tri-Sure steel closures (Optional)
Closing Torque G2= 25 N/m G ¾ = 15 N/m

Additional Specification

- Side Seam - Welded
- End Seams - Double Seamed & Solutioned
- Rolling Hoops - None
- Handle - Strap handle
- Internal Finish - Plain/ Epoxy Phenolic Lacquer
- External Finish - Stoving Enamel



Volume	Steel Plate Thickness (mm)			Weight	UN Approval
15 Litre Nominal	Top End	Body	Bottom	2.4 kg +/- 5%	1A1/X/400/**/GB/2432
	0.6mm +/- .05mm	0.6mm +/- .05mm	0.6mm +/- .05mm		

<i>To test levels of</i>		<i>The packaging is approved as provided in the relevant transport rule, to contain liquids of</i>				
Drop Height (m)	1.8	<i>packaging group</i>		<i>density (d)</i>		
Leakproofness (kPa)	30	I		1.2		
Stacked at 3m with RD(d)	1.8	II		1.8		
Internal Pressure (kPa)	400	III		1.8		
Qty Per Pallet	Pallet Size	Shrink Wrap	Strap	Pallet Hood	Layer Pad	Foam Wrap
96	1100mm x 1100mm	Yes	Optional	Optional	Optional	Optional

N.B. Users should satisfy themselves that the type of drum including all material closures and coatings are suitable and compatible with the products to be contained. Additional UN information can be found on www.vca.org.gov Information on terms & conditions can be found on www.jamesgcarrick.com

This document is uncontrolled when printed.

James G Carrick & Co Ltd
450 Petershill Road
Springburn
Glasgow
G21 4PB

Tel +44 141 558 6008
Fax +44 141 557 0318
e mail sales@jamesgcarrick.com